



????????? ?? ?????????...

140 mm x 210 mm x 53 mm FAG 23028-E1A-K-M + AHX3028

Bearing No. 23028-E1A-K-M + AHX3028

23028-E1A-K-M + AHX3028 Bearing 2D drawings and 3D CAD models

Size	135x210x53 mm
Bore Diameter	135 mm
Outer Diameter	210 mm
Width	53 mm
d_{1H}	135 mm
D	210 mm
B	53 mm
a	5 mm
b	14 mm
D_1	192,3 mm
$D_{a \max}$	201,2 mm
d	140 mm
d_{2G}	M150X2
$d_{a \min}$	148,8 mm
d_s	4,8 mm
l	68 mm
n_s	9,5 mm
$r_{a \max}$	2 mm
r_{\min}	2 mm
	AHX3028 / Designation, withdrawal sleeve
m	6 kg / Weight
m_1	1,03 kg / Weight, withdrawal sleeve



????????? ?? ???????...

C_r	570000 N / Dynamic load rating (radial)
e	0,22
Y_1	3,07
Y_2	4,57
C_{0r}	800000 N / Static load rating (radial)
Y_0	3
n_G	3450 1/min / Limiting speed
n_B	2440 1/min / Reference speed
C_{ur}	76000 N / Fatigue limit load, radial